

# ZU725T

Ultra bright professional installation laser projector



- **7800 lumen DuraCore laser projector - Ultra bright for immersive installations**
- **Full motorized lens shift - Ideal for a simple set-up**
- **Large zoom range - Motorized zoom expands placement opportunities**
- **Long life - Delivers 30,000 hours of virtually maintenance-free operation**



At 7800 lumens with 4K and HDR compatibility, the ZU725T features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include motorized zoom and focus, full motorized lens shift and built-in dual 10W speakers.

High brightness, color precision and quiet operation, alongside a 1.6x zoom make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as simulation, edge-blending and projection mapping, and immersive installations.

## Specifications

UPC: 796435 44 656 7, EAN: 5055387666955, Colour: Black

|                                  |   |
|----------------------------------|---|
| <b>Display/image</b>             |   |
| Display technology               | DLP   |
| Resolution                       | WUXGA (1920x1200)   |
| Brightness                       | 7,800 lumens  |
| Contrast ratio                   | 3,000,000:1   |
| Contrast ratio - full on/off     | 1,100:1   |
| Native aspect ratio              | 16:10   |
| Aspect ratio - compatible        | 4:3,16:9,16:10  |
| Keystone correction - horizontal | 30°   |
| Keystone correction - vertical   | 30°   |
| Uniformity                       | 95%   |
| Screen size                      | 60" ~ 300" diagonal   |
| <b>Lamp info</b>                 |   |
| Light source type                | DuraCore Laser  |
| LASER life                       | 30,000 hours  |
| <b>Optical</b>                   |   |
| Throw ratio                      | 1.25:1 ~ 2:1  |
| Projection distance              | 31.5" - 846.46"   |
| Zoom                             | 1.6   |
| Zoom type                        | Motorised   |
| Focal length (mm)                | 18.72~29.59   |
| Lens shift                       | Vertical: +/-55%, Horizontal: +/-25%  |
| Lens shift                       | Yes - <a href="#">{{downloads_link}}</a>  |
| <b>Connectivity</b>              |   |
| Connections                      | <p><b>Inputs</b> 1 x HDBaseT, 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm</p> <p><b>Outputs</b> 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm</p> <p><b>Control</b> 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232</p> |
| LAN - wireless networking        | No  |
| <b>General</b>                   |   |
| Noise level (typical)            | 34dB  |
| Noise level (max)                | 36dB  |
| 3D                               | Full 3D   |
| Security                         | Security bar, Kensington Lock   |
| OSD / display languages          | 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)   |
| 24/7 operation                   | Yes   |
| 360° operation                   | Yes   |
| Remote control                   | Backlit ProAV remote  |
| Speaker count                    | 2   |
| Watts per speaker                | 10W   |
| <b>Networking</b>                |   |
| LAN - wireless networking        | No  |
| LAN                              | Yes   |
| <b>Power</b>                     |   |
| Power supply                     | AC 90 – 264V 50/60 Hz with PFC input  |
| Power consumption (standby)      | 0.5W  |
| Power consumption (min)          | 260W  |
| Power consumption (max)          | 520W  |
| <b>Weight and dimensions</b>     |   |
| Dimensions (W x D x H)           | 19.13" x 17.03" x 6.93"   |
| Gross weight                     | 38.58 lbs   |
| Net weight                       | 30.86 lbs   |



# ZU820T

Ultra bright professional laser projector

---



- **8800 lumen DuraCore laser projector - Ultra bright for immersive installations**
- **Full motorized lens shift - Ideal for a simple set-up**
- **Large zoom range - Motorized zoom expands placement opportunities**
- **Long life - Delivers 30,000 hours of virtually maintenance-free operation**



At 8800 lumens with 4K and HDR compatibility, the ZU820T features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include motorized zoom and focus, full motorized lens shift and built-in dual 10W speakers.

High brightness, color precision and quiet operation, alongside a 1.6x zoom make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as simulation, edge-blending and projection mapping, and immersive installations.

## Specifications

UPC: 796435 44 601 7, EAN: 5055387666245, Colour: Black

| Display/image                    |   |
|----------------------------------|---|
| Display technology               | DLP   |
| Resolution                       | WUXGA (1920x1200)   |
| Brightness                       | 8,800 lumens  |
| ANSI brightness                  | 7,400   |
| Contrast ratio                   | 3,000,000:1   |
| Contrast ratio - full on/off     | 1,100:1   |
| Native aspect ratio              | 16:10   |
| Aspect ratio - compatible        | 4:3,16:9,16:10  |
| Keystone correction - horizontal | 30°   |
| Keystone correction - vertical   | 30°   |
| Uniformity                       | 95%   |
| Screen size                      | 50" ~ 300" diagonal   |
| Lamp info                        |   |
| Light source type                | DuraCore Laser  |
| LASER life                       | 30,000 hours  |
| Optical                          |   |
| Throw ratio                      | 1.25:1 ~ 2:1  |
| Projection distance              | 31.5" - 846.46"   |
| Zoom                             | 1.6   |
| Zoom type                        | Motorised   |
| Focal length (mm)                | 18.72-29.59   |
| Lens shift                       | Vertical: +/-55%, Horizontal: +/-25%  |
| Lens shift                       | Yes - <a href="#">{{downloads_link}}</a>  |
| Connectivity                     |   |
| Connections                      | <p><b>Inputs</b> 1 x HDBaseT, 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm</p> <p><b>Outputs</b> 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm</p> <p><b>Control</b> 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232</p> |
| LAN - wireless networking        | No  |
| General                          |   |
| Noise level (typical)            | 34dB  |
| Noise level (max)                | 36dB  |
| 3D                               | Full 3D   |
| Security                         | Security bar, Kensington Lock   |
| OSD / display languages          | 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)   |
| 24/7 operation                   | Yes   |
| 360° operation                   | Yes   |
| Remote control                   | Backlit ProAV remote  |
| Speaker count                    | 2   |
| Watts per speaker                | 10W   |
| Networking                       |   |
| LAN - wireless networking        | No  |
| LAN                              | Yes   |
| Power                            |   |
| Power supply                     | AC 90 – 264V 50/60 Hz with PFC input  |
| Power consumption (standby)      | 0.5W  |
| Power consumption (min)          | 260W  |
| Power consumption (max)          | 520W  |
| Weight and dimensions            |   |
| Dimensions (W x D x H)           | 19.13" x 17.03" x 6.93"   |
| Gross weight                     | 38.58 lbs   |
| Net weight                       | 30.86 lbs   |



# ZU920T

Ultra bright professional laser projector

---



- **9800 lumen DuraCore laser projector - Ultra bright for immersive installations**
- **Full motorized lens shift - Ideal for a simple set-up**
- **Large zoom range - Motorized zoom expands placement opportunities**
- **Long life - Delivers 30,000 hours of virtually maintenance-free operation**



At 9,800 lumens with 4K and HDR compatibility, the ZU920T features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include a motorized zoom and focus, full motorized lens shift and built-in dual 10W speakers.

High brightness, color precision and quiet operation make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as edge-blending and projection mapping, simulation, and immersive installations.

## Specifications

UPC: 796435 44 589 8, EAN: 5055387666030, Colour: Black

| Display/image                    |  |
|----------------------------------|--|
| Display technology               | DLP  |
| Resolution                       | WUXGA (1920x1200)  |
| Brightness                       | 9,800 lumens   |
| ANSI brightness                  | 8,200  |
| Contrast ratio                   | 3,000,000:1  |
| Contrast ratio - full on/off     | 1,100:1  |
| Native aspect ratio              | 16:10  |
| Aspect ratio - compatible        | 4:3,16:9,16:10   |
| Keystone correction - horizontal | 30°  |
| Keystone correction - vertical   | 30°  |
| Uniformity                       | 95%  |
| Screen size                      | 50" ~ 300" diagonal  |
| Lamp info                        |  |
| Light source type                | DuraCore Laser   |
| LASER life                       | 30,000 hours   |
| Optical                          |  |
| Throw ratio                      | 1.25:1 ~ 2:1   |
| Projection distance              | 52.36" - 514.17"   |
| Zoom                             | 1.6  |
| Zoom type                        | Motorised  |
| Focal length (mm)                | 18.72-29.59  |
| Lens shift                       | Vertical: +/-55%, Horizontal: +/-25%   |
| Native offset                    | 50%  |
| Lens shift                       | Yes - <a href="#">{{downloads_link}}</a>   |
| Connectivity                     |  |
| Connections                      | <b>Inputs</b> 1 x HDBaseT, 2 x HDMI 2.0, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm<br><b>Outputs</b> 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm<br><b>Control</b> 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 |
| LAN - wireless networking        | No   |
| General                          |  |
| Noise level (typical)            | 36dB   |
| Noise level (max)                | 38dB   |
| Security                         | Security bar, Kensington Lock  |
| OSD / display languages          | 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)  |
| 24/7 operation                   | Yes  |
| 360° operation                   | Yes  |
| Remote control                   | Backlit ProAV remote   |
| Speaker count                    | 2  |
| Watts per speaker                | 10W  |
| Networking                       |  |
| LAN - wireless networking        | No   |
| LAN                              | Yes  |
| Power                            |  |
| Power supply                     | AC 90 – 264V 50/60 Hz  |
| Power consumption (min)          | 260W   |
| Power consumption (max)          | 505W   |
| Weight and dimensions            |  |
| Dimensions (W x D x H)           | 19.13" x 17.03" x 6.93"  |
| Gross weight                     | 38.58 lbs  |
| Net weight                       | 30.86 lbs  |



# ZU725TST

Ultra bright professional installation laser projector

---



- **7200 lumen DuraCore laser projector - Ultra bright for immersive installations**
- **Full motorized lens shift - Ideal for a simple set-up**
- **Large zoom range - Motorized zoom expands placement opportunities**
- **DuraCore laser technology - Delivers 30,000 hours of virtually maintenance-free operation**

At 7200 lumens with 4K and HDR compatibility, the ZU725TST features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include motorized zoom and focus, full motorized lens shift, and built-in dual 10W speakers.

High brightness, color precision and quiet operation, alongside a 1.26x zoom, make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as simulation, edge-blending and projection mapping, and immersive installations.



## Specifications

UPC: 796435 44 669 7, EAN: 5055387667488, Colour: Black

### Display/image

|                                  |                     |
|----------------------------------|---------------------|
| Display technology               | DLP                 |
| Resolution                       | WUXGA (1920x1200)   |
| Brightness                       | 7,200 lumens        |
| ANSI brightness                  | 6,000               |
| Contrast ratio                   | 3,000,000:1         |
| Contrast ratio - full on/off     | 1,100:1             |
| Native aspect ratio              | 16:10               |
| Aspect ratio - compatible        | 4:3,16:9,16:10      |
| Keystone correction - horizontal | 30°                 |
| Keystone correction - vertical   | 15°                 |
| Displayable colors (millions)    | 1073.4              |
| Uniformity                       | 95%                 |
| Screen size                      | 50" ~ 300" diagonal |

### Lamp info

|                   |                |
|-------------------|----------------|
| Light source type | DuraCore Laser |
| LASER life        | 30,000 hours   |

### Optical

|                     |  |
|---------------------|--|
| Throw ratio         | 0.75:1 ~ 0.95:1                          |
| Projection distance | 31.1" - 244.49"                          |
| Zoom                | 1.26                                     |
| Zoom type           | Motorised                                |
| Focal length (mm)   | 11.11 ~ 14.16                            |
| Lens shift          | Vertical: +/-50%, Horizontal: +/-15%     |
| Lens shift          | Yes - <a href="#">{{downloads_link}}</a> |

### Connectivity

|             |   |
|-------------|---|
| Connections | <p><b>Inputs</b> 1 x HDBaseT, 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm</p> <p><b>Outputs</b> 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm</p> <p><b>Control</b> 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232</p> |
|-------------|---|

### LAN - wireless networking

No

### General

|                         |   |
|-------------------------|---|
| Noise level (typical)   | 34dB  |
| Noise level (max)       | 36dB  |
| 3D                      | Full 3D   |
| Security                | Security bar, Kensington Lock   |
| IP rating               | IP5X  |
| OSD / display languages | 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) |
| 24/7 operation          | Yes   |
| 360° operation          | Yes   |
| Remote control          | Backlit ProAV remote  |
| Speaker count           | 2   |
| Watts per speaker       | 10W   |

### Networking

#### LAN - wireless networking

No

#### LAN

Yes

### Power

|                             |                                      |
|-----------------------------|--------------------------------------|
| Power supply                | AC 90 – 264V 50/60 Hz with PFC input |
| Power consumption (standby) | 0.5W                                 |
| Power consumption (min)     | 260W                                 |
| Power consumption (max)     | 520W                                 |

### Weight and dimensions

|                        |                        |
|------------------------|------------------------|
| Dimensions (W x D x H) | 19.13" x 15.53" x 7.3" |
| Gross weight           | 38.58 lbs              |
| Net weight             | 27.78 lbs              |





# ZU820TST

Ultra bright professional short throw laser projector

---



- **8200 lumen DuraCore laser projector - Ultra bright for immersive installations**
- **Full motorized lens shift - Ideal for a simple set-up**
- **Large zoom range - Motorized zoom expands placement opportunities**
- **DuraCore laser technology - Delivers 30,000 hours of virtually maintenance-free operation**

At 8200 lumens with 4K and HDR compatibility, the ZU820TST features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include motorized zoom and focus, full motorized lens shift, and built-in dual 10W speakers.

High brightness, color precision and quiet operation, alongside a 1.26x zoom, make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as simulation, edge-blending and projection mapping, and immersive installations.



## Specifications

UPC: 796435 44 628 4, EAN: 5055387666672, Colour: Black

### Display/image

|                                  |                     |
|----------------------------------|---------------------|
| Display technology               | DLP                 |
| Resolution                       | WUXGA (1920x1200)   |
| Brightness                       | 8,200 lumens        |
| ANSI brightness                  | 6,900               |
| Contrast ratio                   | 3,000,000:1         |
| Contrast ratio - full on/off     | 1,100:1             |
| Native aspect ratio              | 16:10               |
| Aspect ratio - compatible        | 4:3,16:9,16:10      |
| Keystone correction - horizontal | 30°                 |
| Keystone correction - vertical   | 15°                 |
| Displayable colors (millions)    | 1073.4              |
| Uniformity                       | 95%                 |
| Screen size                      | 50" ~ 300" diagonal |

### Lamp info

|                   |              |
|-------------------|--------------|
| Light source type | Laser        |
| LASER life        | 30,000 hours |

### Optical

|                     |  |
|---------------------|--|
| Throw ratio         | 0.75:1 ~ 0.95:1                          |
| Projection distance | 31.1" - 244.49"                          |
| Zoom                | 1.26                                     |
| Zoom type           | Motorised                                |
| Focal length (mm)   | 11.11 ~ 14.16                            |
| Lens shift          | Vertical: +/-50%, Horizontal: +/-15%     |
| Lens shift          | Yes - <a href="#">{{downloads_link}}</a> |

### Connectivity

|             |   |
|-------------|---|
| Connections | <p><b>Inputs</b> 1 x HDBaseT, 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm</p> <p><b>Outputs</b> 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm</p> <p><b>Control</b> 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232</p> |
|-------------|---|

### LAN - wireless networking

No

### General

|                         |   |
|-------------------------|---|
| Noise level (typical)   | 34dB  |
| Noise level (max)       | 36dB  |
| 3D                      | Full 3D   |
| Security                | Security bar, Kensington Lock   |
| IP rating               | IP5X  |
| OSD / display languages | 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) |
| 24/7 operation          | Yes   |
| 360° operation          | Yes   |
| Remote control          | Backlit ProAV remote  |
| Speaker count           | 2   |
| Watts per speaker       | 10W   |

### Networking

#### LAN - wireless networking

No

#### LAN

Yes

### Power

|                             |                                      |
|-----------------------------|--------------------------------------|
| Power supply                | AC 90 – 264V 50/60 Hz with PFC input |
| Power consumption (standby) | 0.5W                                 |
| Power consumption (min)     | 260W                                 |
| Power consumption (max)     | 520W                                 |

### Weight and dimensions

|                        |                        |
|------------------------|------------------------|
| Dimensions (W x D x H) | 19.13" x 15.53" x 7.3" |
| Gross weight           | 38.58 lbs              |
| Net weight             | 27.78 lbs              |



# ZU920TST

Ultra-Bright professional laser projector



- **9,800 Lumen Duracore laser projector - Ultra bright for immersive installations**
- **Full motorized lens shift - Ideal for a simple set up**
- **Large zoom range - Motorized zoom expands placement opportunities**
- **Long life - Delivers 30,000 hours of virtually maintenance-free operation**



At 9,800 lumens with 4K and HDR compatibility, the ZU920TST features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode.

Other features include a motorized zoom and focus, full motorized lens shift, and built-in dual 10W speakers.

## Specifications

UPC: 796435 44 590 4, EAN: 5055387666047, Colour: black

| Display/image                    |  |
|----------------------------------|--|
| Display technology               | DLP  |
| Resolution                       | WUXGA (1920x1200)  |
| Brightness                       | 9,800 lumens   |
| ANSI brightness                  | 8,200  |
| Contrast ratio                   | 3,000,000:1  |
| Contrast ratio - full on/off     | 1,100:1  |
| Native aspect ratio              | 16:10  |
| Aspect ratio - compatible        | 4:3,16:9,16:10   |
| Keystone correction - horizontal | 30°  |
| Keystone correction - vertical   | 30°  |
| Uniformity                       | 95%  |
| Screen size                      | 50" ~ 300" diagonal  |
| Lamp info                        |  |
| Light source type                | DuraCore Laser   |
| LASER life                       | 30,000 hours   |
| Optical                          |  |
| Throw ratio                      | 0.65:1 ~ 0.75:1  |
| Projection distance              | 27.56" - 653.54"   |
| Zoom                             | 1.15   |
| Zoom type                        | Motorised  |
| Focal length (mm)                | 9.69~11.19   |
| Lens shift                       | Vertical: +/-55%, Horizontal: +/-25%   |
| Native offset                    | 50%  |
| Lens shift                       | Yes - <a href="#">{{downloads_link}}</a>   |
| Connectivity                     |  |
| Connections                      | <b>Inputs</b> 1 x HDBaseT, 1 x HDMI 2.0, 1 x HDMI 2.0, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm<br><b>Outputs</b> 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm<br><b>Control</b> 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 |
| LAN - wireless networking        | No   |
| General                          |  |
| Noise level (typical)            | 36dB   |
| Noise level (max)                | 38dB   |
| Security                         | Security bar, Kensington Lock  |
| OSD / display languages          | 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)  |
| 24/7 operation                   | Yes  |
| 360° operation                   | Yes  |
| Remote control                   | Backlit ProAV remote   |
| Speaker count                    | 2  |
| Watts per speaker                | 10W  |
| Networking                       |  |
| LAN - wireless networking        | No   |
| LAN                              | Yes  |
| Power                            |  |
| Power supply                     | AC 90 - 264V 50/60 Hz  |
| Power consumption (min)          | 260W   |
| Power consumption (max)          | 505W   |
| Weight and dimensions            |  |
| Dimensions (W x D x H)           | 19.13" x 16.43" x 6.93"  |
| Gross weight                     | 38.58 lbs  |
| Net weight                       | 30.86 lbs  |

